


WIRING TABLE

CN1		CN2	
KEY		KEY	
1	DRAIN WIRE	1	
2		2	
3		3	
4	DRAIN WIRE	4	
5		5	
6		6	
7	DRAIN WIRE	7	

ELECTRICAL CHARACTER:

- 100% OPEN&SHORT TESTING;
- WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- INSULATION RESISTANCE:10M Ohm(Min);
- CONDUCTIVE RESISTANCE:2 Ohm (Max).

A	INITIAL RELEASE				26/06/22		
REV	DESCRIPTION OF CHANGE				DATE		
TOLERANCE			DIKWAN® 东莞市蔼群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO.,LTD				
INCHES MM							
. X	. 015	. 30					
. XX	. 010	. 10					
. XXX	. 005	. 05	SCALE	NONE		REV	A
DRAWN BY	WXF		UNIT	MM			
CHECK BY			SHEET	1/1	CUSTOMER:		
APPD BY			DATE	26/06/22	DWG NO:		
			TITLE: SATA-SATA				
CUSTOMER P/N:			P/N: 1. AMSSS0010014				

4	LATCH	STAINLESS STEEL	2	PCS
3	MOLDING	45P PVC BLACK	A/R	G
2	CONNECTOR	SATA 7P/F, PIN:G/F	2	PCS
1	CABLE	30AWG*1P+32AWG*2C, OD:0.95*2.25MM, 100±5 ohm	A/R	M
NO.	NAME	SPEC DESCRIPTION	QT'Y	UNIT