



WIRING TABLE			
CN1		CN2	
KEY		KEY	
1	DRAIN WIRE	1	
2		2	
3		3	
4	DRAIN WIRE	4	
5		5	
6		6	
7	DRAIN WIRE	7	

电气特性:

1. 100%开路、短路、断路测试。
2. 绝缘阻抗: 10M Ohm Min
3. 导通阻抗: 2 Ohm MAX
4. 耐压: DC 300V, 0.01/Sec

A	INITIAL RELEASE				26/06/22
REV	DESCRIPTION OF CHANGE				DATE
TOLERANCE INCHES MM			DIKWAN® 东莞市蔼群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO.,LTD		
4	弹片	不锈钢弹片	2	PCS	SCALE NONE UNIT MM SHEET 1/1 DATE 26/06/22 TITLE: SATA-SATA P/N: 1.AMSSS0010014
3	胶料	45P PVC 黑色	A/R	G	
2	连接器	SATA 7P母头, 端子镀金: G/F, 黑色胶芯	2	PCS	
1	线材	30AWG*1P+32AWG*2C, OD:0.95*2.25MM, 100±5 ohm	A/R	M	
NO.	NAME	SPEC DESCRIPTION	QT'Y	UNIT	
			CUSTOMER P/N:		